

PRICE LIST FOR HF-VENEER PRESSES

manual-hydraulic with double-heave hand pump

valid from 01.04.2021

Type		EURO
H 30	press surface 220 x 102 cm , 3 cylinders, heave 35 cm	
	press pressure 30 tons = 1,5 kg/cm ²	
H 30 S	standard version	7 200,00
H 30 A	with aluminium sheeting	8 200,00
H 30 W	heated with water, connected left or right, type HF	10 500,00
H 30 E	with electric heating plates à 5 kW	12 800,00
<i>accessories:</i>	extra charge on model with gold eloxal surface of the electric heating plates	730,00
	extra charge on model for disassembly	980,00
H 40	press surface 220 x 110 cm , 4 cylinders, heave 35 cm	
	press pressure 40 tons = 1,7 kg/cm ²	
H 40 S	standard version	9 400,00
H 40 A	with aluminium sheeting	10 400,00
H 40 W	heated with water, connected left or right, type ELKOM	13 200,00
H 40 E	with electric heating plates à 5 kW	14 600,00
<i>accessories:</i>	extra charge on model with gold eloxal surface of the electric heating plates	800,00
	extra charge on model for disassembly	1 100,00

Costs of installation upon agreement. Prices for other sizes or technical modifications on demand.
All prices quoted are ex works without VAT, without duty. Guarantee 2 years.

EXPLANATORY SUPPLEMENT TO PRICE-LIST

MANUAL-HYDRAULIC PRESS: closed by the fast heave of the double-heave hand pump, building up pressure by the slow heave, opening by turning the hand-wheel

FULLY HYDRAULIC PRESS: cog-wheel pump driven by 2,2 kW electric motor. If the press pressure falls below set level, the automatic switch builds up pressure again automatically.

STANDARD CONSTRUCTION: delivered with two 38mm panels of uncovered chipboard so that the customer pays a competitive price and has the individual choice of gluing on sheets of plastic or aluminium.

PRESS WITH ALUMINIUM SHEETING: 38mm plates of chipboard on which aluminium sheets are screwed at the edges, plates covered on all four sides.

PRESS WITH HF-WATER HEATING PLATES: heating elements built into chipboard, connected (as requested when ordering) either left or right, covered with aluminium sheets with screw edges, suitable for connection to already existing central heating system. Pipe thread 1/2".

PRESS WITH WATER HEATING PLATES MADE OF ALUMINIUM PROFILES:

Over size of 220 x 110 cm press surface we use a construction of aluminium profiles and aluminium sheeting. Surface off screws and rivets. Type ELKOM ÖKOTHERM.

PRESS WITH ELECTRIC HEATING PLATES: sheets of 9mm full aluminium, surface of press off screws and rivets, therefore optimal use for single pressing or guided work. Pre-heating approx. 15 min. at 100 degree. Regulation of temperature by two point thermostat and protective mechanism with control lamp.

MODEL FOR DISASSEMBLY: If the customer wishes to assemble the press, it is delivered assembled. (Disassembly by the customer himself simplifies correct reassembly). Parts: upper part of press + press table, cylindrical supports, two pairs of legs, plates as ordered. For mounting by our company the cost is calculated on working hours and the distance. Additionally 2 - 3 helpers must be available for approx. one hour. Please ask for fixed quotation.

Quotations for special presses on demand!